

40G QSFP+ Direct Attach Active Copper Cables

GQS-AC400-xxC

Features

- 4-channel full-duplex active copper cable
- SFF-8436 compliant QSFP+ connectors
- SFF-8636 compliant I2C management interface
- Data rate up to 40Gbps (4x 10Gbps)
- Copper link length up to 10m (active limiting)
- Excellent signal integrity and low insertion loss
- Operating case temperature range: 0°C to +70°C
- Single 3.3V supply voltage
- RoHS compliant



Applications

- 40G Ethernet 40GBASE-CR4
- SAS, servers, hubs, switches and routers



Product Description

The 40G QSFP+ direct attach active copper cable assemblies are a high-performance and cost-effective I/O solution for LAN, HPC and SAN applications. The high speed cable assemblies meet and exceed 40G Ethernet commercial temperature requirements for performance and reliability. The cables are compliant with InfiniBand architecture, SFF-8436 specifications and provide connectivity between devices using QSFP ports.

Recommended Operating Conditions


Parameter	Symbol	Min	Typical	Max	Unit
Storage Ambient Temperature		-40		+85	°C
Operating Case Temperature	T _c	0		+70	°C
Power Supply Voltage	V _{CC3}	3.14	3.3	3.47	V
Power Dissipation	PD			2.5	W
Data Rate Per Lane		1		10	Gb/s

Mechanical Dimensions




代码	长度范围 (m)	公差 (cm)
L	$L < 0.5$	± 3
	$0.5 < L < 5$	± 5
	$5 < L < 20$	± 8
	$20 < L$	± 10

QSFP+ Host Board Schematic for active copper cables



Pin Descriptions



Top Side
Viewed From Top

Bottom Side
Viewed From Bottom

Pin	Logic	Symbol	Name/Description	Notes
1		GND	Ground	1
2	CML-I	Tx2n	Transmitter Inverted Data Input	
3	CML-I	Tx2p	Transmitter Non-Inverted Data Input	
4		GND	Ground	1
5	CML-I	Tx4n	Transmitter Inverted Data Input	
6	CML-I	Tx4p	Transmitter Non-Inverted Data Input	
7		GND	Ground	1
8	LVTTTL-I	ModSelL	Module Select	
9	LVTTTL-I	ResetL	Module Reset	
10		Vcc Rx	+3.3V Power Supply Receiver	2
11	LVC MOSI/O	SCL	2-wire serial interface clock	
12	LVC MOSI/O	SDA	2-wire serial interface data	
13		GND	Ground	1
14	CML-O	Rx3p	Receiver Non-Inverted Data Output	
15	CML-O	Rx3n	Receiver Inverted Data Output	
16		GND	Ground	1

17	CML-O	Rx1p	Receiver Non-Inverted Data Output	
18	CML-O	Rx1n	Receiver Inverted Data Output	
19		GND	Ground	1
20		GND	Ground	1
21	CML-O	Rx2n	Receiver Inverted Data Output	
22	CML-O	Rx2p	Receiver Non-Inverted Data Output	
23		GND	Ground	1
24	CML-O	Rx4n	Receiver Inverted Data Output	
25	CML-O	Rx4p	Receiver Non-Inverted Data Output	
26		GND	Ground	1
27	LVTTTL-O	ModPrsL	Module Present	
28	LVTTTL-O	IntL	Interrupt	
29		Vcc Tx	+3.3V Power supply transmitter	2
30		Vcc1	+3.3V Power supply	2
31	LVTTTL-I	LPMode	Low Power Mode	
32		GND	Ground	1
33	CML-I	Tx3p	Transmitter Non-Inverted Data Input	
34	CML-I	Tx3n	Transmitter Inverted Data Input	
35		GND	Ground	1
36	CML-I	Tx1p	Transmitter Non-Inverted Data Input	
37	CML-I	Tx1n	Transmitter Inverted Data Input	
38		GND	Ground	1

Note 1: GND is the symbol for signal and supply (power) common for the QSFP+ module. All are common within the QSFP+ module and all module voltages are referenced to this potential unless otherwise noted. Connect these directly to the host board signal-common ground plane.

Note 2: Vcc Rx, Vcc1 and Vcc Tx are the receiver and transmitter power supplies and shall be applied concurrently. Requirements defined for the host side of the Host Edge Card Connector are listed in Table 6. Recommended host board power supply filtering is shown in Figure 4. Vcc Rx Vcc1 and Vcc Tx may be internally connected within the QSFP+ Module module in any combination. The connector pins are each rated for a maximum current of 500 mA.

Ordering information

Part Number	GQS-AC400-xxC
-------------	---------------



Length (meter)	1	2	3	4	5	6	7	8	9	10
American Wire Gauge (AWG)	30	30	30	30	30	26	26	26	26	26

Note: diameter and distance can be customized.

Example:

GQS-AC400-05C: AWG30, 5 meters;
GQS-AC400-07C: AWG26, 7 meters;
GQS-AC400-10C: AWG26, 10 meters.

Important Notice

Performance figures, data and any illustrative material provided in this data sheet are typical and must be specifically confirmed in writing by GIGALIGHT before they become applicable to any particular order or contract. In accordance with the GIGALIGHT policy of continuous improvement specifications may change without notice. The publication of information in this data sheet does not imply freedom from patent or other protective rights of GIGALIGHT or others. Further details are available from any GIGALIGHT sales representative.

Shenzhen Gigalight Technology Co., Ltd

Headquarter Address: 17F, Zhongtai Tiancheng, Dongbin Rd, Nanshan Shenzhen, Guangdong, Province, China, Zip Code 518067

Tel: +86-755-26734300

Fax: +86-755-26738181

Email: sales@gigalight.com

<https://www.gigalight.com/>